


# Green Infrastructure Stormwater Management Options in an Ultra-Urban Redevelopment


Sandy Doyle-Ahern  
sdoyleahern@emht.com

- + The City of Columbus' Downtown Business Plan was developed in 2002 with the goal of revitalizing the downtown area for the Bicentennial Celebration in 2012.
- + The revitalization of the district will see the creation of a dense, mixed use urban neighborhood.
- + The development plan for the district includes a mixture of condominiums, lofts, and apartments at multiple price points.
- + Neighborhood retail is planned for the district to support the influx of residents.
- + Government offices and civic buildings will bring workers and visitors to the district.

- + A significant challenge in the development of the RiverSouth district has been inadequate infrastructure to meet the needs of a high density, mixed use neighborhood.
- + Existing waterlines and sewers are at or beyond their life expectancy and do not contain the additional capacity required to support the revitalization.
- + Most roadways in the district are one-way, which in general tend to experience higher traffic volumes, higher speeds and larger free-flow speeds than an equivalent two-way road.
- + While the existing roadway network performs well in conveying peak hour traffic demands, it has the adverse effect of creating an inhospitable environment for residents, workers, and shoppers during all other hours of the day.

- + The RiverSouth District consists of approximately 39 acres.
- + The area currently does not have stormwater quantity or quality controls and is drained by a mix of combined sewers and storm sewers.
- + With redevelopment, combined sewers will be disconnected and all stormwater will drain directly to the Scioto River.
- + Stormwater quantity and quality controls are required for redevelopment projects as defined in the City of Columbus Drainage Manual.





Riversouth Phase 2 Area Map

## Water Quality Summary

Phase II River South R/W: 4.81 acres

Treatment Requirement: 20%  
 Required treatment Area: .96 acres

EPA Classifications: Ultra-urban  
 Tributary to 4th Order Stream  
 Redevelopment


The EPA requires that 20% of the area be treated for water quality or a 20% decrease in impervious area or some combination of the two.

Additional widening on the south side of Main Street between the Main Street bridge and Civic Center Drive may be performed. Alternative geometrics are being prepared for review by Public Service. If this widening is required, an additional 0.1 acre of disturbance shall be added to the calculations presented above.



# Stormwater Management Options by Density

+Best Management Practice (BMP)



	+Low Density	+Medium Density	+High Density	+Town Center
Bioretention / Rain Garden	□	□	□	□
Detention (Dry Basin)	□	□		
Detention (Wet Basin)	□	□		
Detention (Underground Storage)			□	□
Vegetated Swale	□	□		
Manufactured Systems			□	□
Pervious Pavement			□	□
Stormwater Wetland	□	□		
Vegetated "Green Roof" System			□	□

# Low Impact Development Controls



Permeable Pavement - unit pavers, concrete or asphalt systems designed for storage, conveyance, and treatment of stormwater.

- + Lower life-cycle costs versus concrete or asphalt
- + Upfront capital costs are higher
- + Infiltrate up to 400 inches per hour
- + Construction sequencing very important



Bioretention – includes Rain Gardens, using landscaping and soils for water quality and quantity control.

- + Reduces runoff volume, metals, nutrients and thermal impacts of runoff
- + Can look identical to traditional landscaped areas
- + Landscaping costs can be higher than traditional site for native plants



+Indianapolis, IN









## Attributes


- + Reduces volume of runoff
- + Reduces concentrations of metals and nutrients
- + Temperature reduction of runoff
- + Aesthetically pleasing, appears to be a normal landscaped area
- + Meets most local and national post-construction water quality standards
- + Promotes groundwater recharge



## Concerns

- + Costs can be high depending on the local availability of engineered soil if the basin is installed in an area with clayey soils
- + Requires more maintenance than a wet pond, but is very similar to a typical landscape bed
- + Construction oversight and sequencing is a major issue during construction







+ Build with soils to meet local requirements. Can infiltration work or is an impermeable basin necessary?




Underground Congestion.

+ Infiltration BMP selection process schematic example



Milwaukee BMP Performance



+Data Courtesy of the Center For Neighborhood Technology


+ The Portland Bureau of Environmental Services performed an effectiveness evaluation of all the BMPs currently in use in the City.



+ Photo courtesy of Portland Bureau of Environmental Services

+ **Bioswales on Portland's Division Street**

### Portland BMP Performance



+ Data Courtesy of the Center For Neighborhood Technology



+ Analyzing 5 years of historical rain records, the bioretention rain gardens designed and constructed in the Phase 1 - Alabama Street (1/2 street only) provided the following results for potential CSO abatement:


+ 100% of all rain events about an inch or less are stored, infiltrated and removed from the Combined Sewer System

+ On average, the bioretention areas for all rain events will remove 240,000 gallons of rain runoff annually.



+ This equates to keeping 91% of all annual rainfall runoff from the combined sewer system.








Bioretention Surface Area as Percentage of Impervious Area Tributary to Basin



- + The RiverSouth District consists of approximately 39 acres.
- + The area currently does not have stormwater quantity or quality controls and is drained by a mix of combined sewers and storm sewers.
- + With redevelopment, combined sewers will be disconnected and all stormwater will drain directly to the Scioto River.
- + Stormwater quantity and quality controls are required for redevelopment projects as defined in the City of Columbus Drainage Manual.



Water Quality Options:	A	B	C	D	E	F	G	H	WP
<b>Economy</b>									
Low construction cost	■	■	■	■	■	■	■	■	
Ease of utility coordination and relocation	■	■	■	■	■	■	■	■	
Low maintenance	■	■	■	■	■	■	■	■	
Little or no irrigation required <sup>1</sup>	■	■	■	■	■	■	■	■	
Ease of design and construction	■	■	■	■	■	■	■	■	
Ease of access and repair	■	■	■	■	■	■	■	■	
Economy Subtotal:	14	14	9	8	7	19	20	22	
<b>Environment</b>									
Streetscape appearance	■	■	■	■	■	■	■	■	
Quality planting environment: Trees	■	■	■	■	■	■	■	■	
Quality planting environment: Planters	■	■	■	■	■	■	■	■	
Meets OEPA requirements	■	■	■	■	■	■	■	■	
Provides water quality benefit	■	■	■	■	■	■	■	■	
Allows for infiltration <sup>2</sup>	■	■	■	■	■	■	■	■	
Visible to public as green infrastructure	■	■	■	■	■	■	■	■	
Allows trees to access roadway SW	■	■	■	■	■	■	■	■	
Environment Subtotal:	21	25	32	30	30	22	7	8	
<b>Total:</b>	<b>35</b>	<b>39</b>	<b>41</b>	<b>38</b>	<b>37</b>	<b>41</b>	<b>27</b>	<b>30</b>	

- Not Applicable / 0
- Poor / 1
- Fair / 2
- Good / 3
- Excellent / 4

Key of Water Quality Options:

**A: Phase 1 Design**

Current Riversouth Phase 1 Design

**B: Modified Phase 1 Design**

Riversouth Phase 1 Design modified to allow infiltration and share stormwater with street tree plantings.

**C: Silva Cells with Bioretention Basin**

Silva Cells used to support bioretention walls and share stormwater with street tree plantings.

**D: Silva Cells with Infiltration Gutter and bioretention under sidewalk**

Modified ODOT exfiltration trench detail.

**E: Silva Cells with Pervious Pavers and bioretention under sidewalk**

Pervious pavers are currently not approved for use in ROW.

**F: Shallow Rain Garden**

May provide WQ benefit, but does not meet OEPA requirements for soil profile design. Use with other options.

**G: Proprietary System, i.e. Filterra**

May provide WQ benefit, but may not be approved by OEPA. Shown for comparison, not a recommended option.

**H: Hydrodynamic Device**

Shown for comparison, not a recommended option.

Notes:

1. Supplemental irrigation is recommended for all vegetated options including bioretention basins, rain gardens and street trees.
2. Open bottom options will allow for infiltration, but actual infiltration will be limited by the native subgrade condition. A piped underdrain system is recommended for all open bottom options.



*Shrubs*

- + Sixteen Candles Summersweet
- + Densa Compact Inkberry
- + Jim Dandy Winterberry
- + Red Sprite Winterberry
- + Silver Sprite Bayberry
- + Silver Sprite Bayberry - Pollinator
- + Alfredo American Cranberry Bush

*Ornamental Grasses*

- + Creeping Lily Turf
- + Heavy metal switch grass
- + Upright switch grass

- + The bioretention basins will be constructed of cast-in-place concrete. To provide high quality finish the concrete will be integrally colored and sandblasted.
- + Basins with deep and narrow storage areas will be enclosed with an ornamental steel fence. This fence was selected for its superior coating to resist salt spray corrosion and for its ornamental style.

- + Current 2009 estimate is \$12,500 per water quality unit with plantings at an additional \$22/square foot.
- + Total cost for 25 basins on Main Street and 20 on Rich Street is \$562,500.



Task	Frequency	Note/Comments
Watering	Determined by automatic ET control system	Based on irrigation plan
Fertilization	Once at installation	
Pruning	1-2 times per year	
Mulching	Annually	
Mulch removal	2-3 years	Excess mulch decreases soil infiltration rate and reduces rain water storage volume
Up-Keep	Periodically, as needed	Weeding, trash removal and the removal and replacement of dead plants

- + A fully established vegetated bioretention area still has infiltration capabilities (albeit reduced as compared to summer)
- + The plants and associated root systems still assist with infiltration even during dormancy.
- + Bioretention systems typically require a 3-4 inch shredded hardwood mulch, which provides an insulating layer (however minor) that assists with maintaining infiltration.
- + A specific winter bioretention system infiltration study on systems in Minnesota support this premise.











# +Questions?

## Special acknowledgment to:

City of Columbus, Department of Public Utilities

City of Columbus, Department of Public Service

### EMH&T Staff:

Travis Eifert, PE

Miles Hebert, PE

Rob Ferguson, PE

Doug Turney, PE, LEED

Franco Manno, LEED

Brian Neilson, PE, LEED



5500 New Albany Road . Columbus . Ohio . 43054

8790 Governor's Hill Drive . Suite 110 . Cincinnati . OH . 45249

7400 North Shadeland Ave. . Suite 150 . Indianapolis . IN . 46250

301 McCullough Drive . Suite 109 . Charlotte . NC . 28262

655 Engineering Drive . Suite 150 . Norcross . Georgia . 30092

[www.emht.com](http://www.emht.com)