



Pelletization of Thermal Dried Sludge to Improve Usability and Marketability of Biofertilizer

Meg Hollowed, Process Engineer

Damon Forney

Sudhakar Viswanathan

Wes Yellin

WATER TECHNOLOGIES

Meet the Team



Wes Yellin



Damon Forney



Sudhakar Viswanathan




Western Wake Regional Water Reclamation Facility

WATER TECHNOLOGIES

Wake County Water Reclamation

- ❖ Wake County
- ❖ 860 sq. miles
- ❖ Raleigh
- ❖ County
- ❖ Raleigh
- ❖ cities in
- ❖ Just over



Western Wake Regional Water Reclamation Facility




- ❖ ~19 employees
- ❖ ~18 MGD liquid treatment
- ❖ Serves: Apex, Cary, Morrisville



Western Wake Regional Water Reclamation Facility

- Prior to drying at Western Wake
 - *Lime stabilization*
- High temp thermal drying at South Cary WRF
 - *North Cary WRF*
 - *Apex WRF*



Considered Technologies

Considered Technologies

- Considered various technologies during planning phase
 - ~~Keep Lime Stabilization (do nothing)~~
 - ~~Digestion~~
 - Thermal Drying
 - ✓ ~~X~~ High, low or somewhere in between
- Drivers included
 - Safety
 - End product quality
 - Cost



Selection


Thermal Drying

- How do dryers differ?
 - *Temperature*
 - *Feed system*
 - *Condensate system*
 - *Belt materials*
 - *Fans and blowers*



Thermal Drying

Treatment Range



Thermal Drying - Belt dryers

Feed System

- Hopper/sifter
- Single depositor
- Multiple depositors

Concerns:

- Single point of failure
- Dryer downtime



Photo Source:

<http://2gryphon.com/technology/modular-design-reduced-costs/>
https://www.huber-technology.com/fileadmin/huber-technology/documents/pdf/pro_bt_usa.pdf

Thermal Drying - Belt dryers



- Dryer continues to operate uninterrupted with one dosing pump out of service
- Clogged depositors can be identified by looking into the dryer
- The clogged depositor can be isolated, removed, cleaned without interrupting the dryer

Thermal Drying - Belt dryers

Condensate system

- Vertical Condensation
- Horizontal Condensation
- Condenser Coils




Photo Source:



<http://2gryphon.com/technology/modular-design-reduced-costs/>
https://www.huber-technology.com/fileadmin/huber-technology/documents/pdf/pro_bt_usa.pdf



Thermal Drying - Belt dryers

Belt Material

- Plastic mesh
 - *150 C max temp*
 - Risk of melting/burning with temperature excursions
 - *Low porosity*
 - Fans
 - Clogging
- Stainless Steel
 - *Long lasting*
 - Can replace only section of belt
 - *High porosity*
 - *Doors/access ports for service/viewing*




Photo Source:

https://www.huber-technology.com/fileadmin/huber-technology/documents/pdf/pro_bt_usa.pdf

Thermal Drying - Belt dryers

Fans and Blowers

- BioCon has 3 - 6 fans
 - *For circulating air within dryer*
 - *Located for easy maintenance*
- Other
 - *Forced air fans*
 - *Must overcome higher headloss through belt*
 - *Located on top of dryer*




Photo Source:

https://www.huber-technology.com/fileadmin/huber-technology/documents/pdf/pro_bt_usa.pdf

Medium Temperature Belt Dryer

Dust and Energy

Low Air Flow
No agitation or back
mixing

Safety

Medium Temperature
Indirect Drying


Odor Control

Low Exhaust Air
Negative Pressure

- Design minimizes noise, odor and dust production
 - Safe, simple and efficient
- Easy access for maintenance and sampling
 - Easy replacement and unclogging of nozzles
- Minimal operator intervention
- Remote monitoring capability
- Local support from Cary, NC

Economic Analysis

	St
Dry Ton, Sludge	
Dry Ton, Chem Sludge	
VS, %	
VSR, %	
DS, End Product	
End Product, WT/yr	
End Product, DT/yr	
Disposal Cost/Revenue per Ton	
Annual Cost/Revenue (WT/yr)	(\$
Annual Cost/Revenue (DT/yr)	(\$






Solution


WATER TECHNOLOGIES

BioCon[®] Medium Temperature Dryer



Air-to-Air Heater

- Plate and Frame Heat Exchanger
- Dryer air exits dryer cabinet and enters air heater via ductwork
- Dryer air exits air heater via ductwork returning to the dryer
- Flue gas exhausted to the stack



BioCon[®] Scope



Safety Equipment

Sprinkler system

- Installed inside dryer in case of a “thermal event”
- Activated by high temperature switches
- Sprinkler has separate valves for warm zone and end zone

Infrared level Switches

- Detect sludge back up in the system

Belt Speed Guards

- Detect solids are not moving adequately through the system


End Product

- N₂ inerting
- Bag house for dust collection

BioCon[®] Design

- Design:
 - *3,800 lb/hr evaporative load per dryer (7,600 lb/hr total)*
 - *~34,000 wet tons per year (15-18%DS)*
 - *Ability to incorporate imported sludge with native*
 - *Recirculation lines on wet cake silos*
 - *Dryer bypass*
- Commissioning completed 2015
- Product sold and transported off-site by outside vendor for soil amendment

BioCon[®] Operation




Current Operation:


- Dewater native sludge
- Mix liquid sludge from Apex with native before dewatering
- One dryer operates 3-4 days per week

BioCon[®] Operation

- Daily sludge to dewatering
- Silo provides temporary wide spot between dewatering and drying



BioCon[®] Performance



Summary

- Ideal solution for achieving Class A without digestion
- Easily store dry product over winter months
- Growing bio-fertilizer market has potential for generating revenue

	Units	Before Drying	After Drying and Pelletizer
Sludge Receiving	\$/gallon	\$0.03	\$0.03
Revenue from 3rd Party Sale	\$/DT	-\$40.00	\$12.00
Revenue from Private Sale	\$/DT	N/A	\$50.00

Questions



Meg Hollowed

meg.hollowed@veolia.com

Sudhakar Viswanathan

sudhakar.viswanathan@veolia.com

Delivery & Installation

Delivery & Installation



Delivery & Installation



Delivery & Installation



Delivery & Installation



Delivery & Installation



Delivery & Installation

